

SELECTION & SPECIFICATION DATA

Type	Non-fibered Asphalt Emulsion Concrete Primer
Description	Blackhawk 7010 Roof Primer is a water-based, asphalt roof primer for concrete substrates. It is designed to provide excellent surface conditions for hot-applied asphaltic membranes.
Features	<ul style="list-style-type: none"> • Extremely low VOCs • Single-component • Cold-applied
Uses	Concrete primer for asphalt roofing
Color	Brown applied, dries black
VOC Value(s)	<10 g/L (0.09 lbs/gal)
Limitations	Protect from freezing. Not for immersion service.

SUBSTRATES & SURFACE PREPARATION

All	Surfaces must be clean and dry. Remove all dirt, dust, oil and other contaminants.
------------	------------------------------------------------------------------------------------

MIXING & THINNING

Mixing	Mix before application to ensure consistency
Thinning	Do not thin
Cleanup	Wet product can be cleaned up using water. Dried material may be cleaned using mineral spirits or an equivalent solvent.

APPLICATION GUIDANCE

Brush	Wide, fiber brush
Roller	Low-nap phenolic core roller

SAFETY

Safety	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
Ventilation	Use in well ventilated areas

PACKAGING, ESTIMATING & HANDLING

ITEM #	PRODUCT	PACKAGING
K-7010-005-001-PL	Blackhawk 7010 Roof Primer	Pail - 4.7 gallons
K-7010-053-001	Blackhawk 7010 Roof Primer	Drum - 53 gallons

Theoretical Coverage Rate	300 – 400 square feet per gallon depending on surface porosity
----------------------------------	----------------------------------------------------------------

Storage & Shelf Life	Estimated shelf life is 6 months when stored in a dry area at 75°F (24°C). Actual shelf life may vary with storage conditions. Do not store below 40°F (4°C) or above 110°F (43°C). Store indoors. Always inspect the product prior to use to ensure proper uniformity.
---------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

TYPICAL PHYSICAL PROPERTIES

Density	8.2 lbs/gal
Solids, by volume	30%
Dry time, at 75°F (25°C)	1 hour or less

Rev 07/22

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.